

PRODUCTS CATALOGUE

Tea Blender (Drum Type)



"Into the Future with Green Tea" **Kawasaki Kiko Co., Ltd.**

Tea blender (drum type) specifications

Can feed during blending, space-saving for tea blending site

Feed evenly

Feed method is rotating spiral feeding where the chute moves in circles in the drum and the chute rotates. It settles in the drum evenly.



Robust and efficient drive

Efficient drive unit equipped with a removal speed dial to adjust the drum rotation speed based on storage volume.



Feed during removing

Mincing is performed linked with the post-process bagging unit, but it can also operate independently.

It can also be fed during blending (or removal).

Simple and easy-to-use control panel



* Tea blender (drum type) specifications

Standard -	Machine dimensions (m)				Maximum capacity	Removal time	Power (kW)			
	Width	Depth	Height	Drum inner diameter	(kg)	(min)	Main unit	Feeding chute	Untangling unit	Removal vibrator
1500K	2.55	2.38	3.50	2.25	1500	20-60	0.4	0.1	0.75×2	0.2
2500K	3.10	2.93	3.50	2.80	2500	35-100	0.4	0.1	0.75x3	0.2
4000K	3.10	2.93	4.40	2.80	4000	35-100	0.4	0.1	0.75x3	0.2

* Note that specifications and appearance are subject to change without notice in order to improve the machine.

Kawasaki Kiko Co., Ltd.

Sales Headquarters:

810-1, Suberikawa, Dategata,

Kakegawa City, Shizuoka Prefecture

436-0005 JAPAN

Phone: +81-537-27-1791 Facsimile: +81-537-27-1716

Website http://www.kawasaki-kiko.co.jp

Dealer