

PRODUCTS CATALOGUE

Secondary Tea Rolling Dryer Hyper

With new 80° pressing arm, one step forward to the ideal tea.



Secondary tea rolling dryer Hyper specifications

Twisting firmly, shaping into sharp tea leaves

Functions

- * New 80o pressing arm, twisting type pressing arm employed
- * Hyper control panel is installed to provide air volume control, temperature control, and removal record tracking functions.
- * Moisture meter installed as standard.
- * 4-piece-divided exhaust metallic net for easy cleaning (with cleaning brush)
- * Dust collection unit installed as standard.

Features

- * New 80o pressing arms are employed for pressing arm to operate immediately after the previous pressing arm releases tea leaves. This maximizes the rolling effect in the same space, and improves shape and color.
- * Spacious drum volume to improve quality and efficiency.
- * Stable product manufacturing can be realized by controlling the hot air volume.

Secondary tea rolling dryer Hyper specifications

Standard	Specifications	Machine dimensions (m)			Drum volume	Drum revolutions	Feeding volume	Required power
		Width	Depth	Height	(m ³)	per minute (rpm)	(fresh leaf) (kg)	(kW)
35K	35K	1.82	1.22	1.97	0.60	22~28	30 ~ 35	0.4 0.2×2
60K	60K-A(Full automatic type)	2.03	1.21	1.87	0.92	21~30	50~60	0.75 0.4×2
	60K-MW(Microcomputer type with moisture meter)							
90K	90K-A(Full automatic type)	2.17	1.51	2.34	1.23	19~27	75 ~ 90	0.75×2 0.55
	90K-MW(Microcomputer type with moisture meter)							
120K	120K-A(Full automatic type)	2.42	1.67	2.46	1.89	17 ~ 25	90~120	1.0 0.75×2
	120K-MW(Microcomputer type with moisture meter)							
200K	200K-A(Full automatic type)	2.68	2.10	2.95	3.15	16~23	150~200	2.2 1.5 1.0
	200K-MW(Microcomputer type with moisture meter)							
240K	240K-A(Full automatic type)	2.77	2.15	2.92	3.71	16 ~ 23	150 ~ 240	2.2 1.5 1.0
	240K-MW(Microcomputer type with moisture meter)							

^{*} Note that specifications and appearance are subject to change without notice in order to improve the machine.

Kawasaki Kiko Co., Ltd.

Sales Headquarters: 810-1, Suberikawa, Dategata, Kakegawa City, Shizuoka Prefecture 436-0005 JAPAN

Phone: +81-537-27-1791 Facsimile: +81-537-27-1716

Website http://www.kawasaki-kiko.co.jp

Dealer